

# PRODUCT DATASHEET



## OX-ON Flexible | Supreme 1600

- Extremely durable
- Very comfortable
- A secure and precise grip
- Oeko-Tex certified
- Best selling glove



| CATEGORI                                                                          | EN-STANDARD                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                   |       |     |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |
|-----------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|-------|-----|--|---------------------|---|-----|----------------------|---|-----|-----------------|---|-----|---------------------|---|-----|--------------------|---|-----|-------|--|--|
| <div><div>CE</div><div>CAT II</div></div>                                         | <div>EN388:2016</div> <table><tr><th rowspan="7"></th><th colspan="3">Level</th></tr><tr><td>Abrasion resistance</td><td>4</td><td>1-4</td></tr><tr><td>Blade cut resistance</td><td>1</td><td>1-5</td></tr><tr><td>Tear resistance</td><td>3</td><td>1-4</td></tr><tr><td>Puncture resistance</td><td>1</td><td>1-4</td></tr><tr><td>TDM Cut resistance</td><td>X</td><td>A-F</td></tr><tr><td>4131X</td><td></td><td></td></tr></table> |  | Level |     |  | Abrasion resistance | 4 | 1-4 | Blade cut resistance | 1 | 1-5 | Tear resistance | 3 | 1-4 | Puncture resistance | 1 | 1-4 | TDM Cut resistance | X | A-F | 4131X |  |  |
|  | Level                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                   |       |     |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |
|                                                                                   | Abrasion resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                   | 4     | 1-4 |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |
|                                                                                   | Blade cut resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                   | 1     | 1-5 |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |
|                                                                                   | Tear resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                   | 3     | 1-4 |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |
|                                                                                   | Puncture resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                   | 1     | 1-4 |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |
|                                                                                   | TDM Cut resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                   | X     | A-F |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |
|                                                                                   | 4131X                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                   |       |     |  |                     |   |     |                      |   |     |                 |   |     |                     |   |     |                    |   |     |       |  |  |

| MATERIALS                | PREPACKAGING / MIN. SALESQUANTITY      |
|--------------------------|----------------------------------------|
| 45% Nitrile<br>25% Nylon | 144 pair per. Colli / 12 pair per. Bag |

| ART no. | EAN           | DB      | FINFO   | SIZE |
|---------|---------------|---------|---------|------|
| 170.66  | 5701952170661 | 1838378 | 7021441 | 6    |
| 170.67  | 5701952170678 | 1702198 | 7021442 | 7    |
| 170.68  | 5701952170685 | 1702201 | 7021443 | 8    |
| 170.69  | 5701952170692 | 1702204 | 6336994 | 9    |
| 170.70  | 5701952170708 | 1702205 | 7021444 | 10   |
| 170.71  | 5701952170715 | 1702207 | 7021445 | 11   |
| 170.72  | 5701952170722 | 1883225 | 7021446 | 12   |

| SHORT DESCRIPTION                                                                                              |
|----------------------------------------------------------------------------------------------------------------|
| The OX-ON Flexible Supreme 1600 is a durable and elastic glove with a perfect fit.                             |
| A breathable flexible glove. Finger-dipped knitted glove for great comfort as well as a precise and safe grip. |
| Flexible Supreme 1600 is Oeko-Tex certified and therefore completely free of hazardous chemicals and dyes.     |



DESIGNED TO PROTECT

OX-ON A/S  
Egelund 23  
DK-6200 Aabenraa

+45 7431 1888  
info@ox-on.dk  
www.ox-on.com