

tesafilm® PAPER

Product Information

59215, 59218, 59212, 59211, 59213, 59217, 59216

Product Description

The transparent tesafilm® PAPER adhesive tape is 67% paper-based (excluding core and packaging), perfect for wrapping, securing, labeling, or repairing. It's nearly invisible on light-colored surfaces as well as hand-tearable and can be written on. Made of paper from well-managed, certified forests and other controlled sources.

Sustainable Aspects

- Tape contains 67% paper (excluding core and packaging), a renewable material. Certified by DIN CERTCO (Registration no. 8C428), part of the TÜV Rheinland Group.
- INGEDE Method 12 certified: does not hinder the recycling of paper and cardboard.
- Made with FSC®-certified paper (FSC® C148769) from responsibly managed forests.

Product Features

- The first transparent tesafilm® PAPER made of 67% paper, a renewable material (excluding core and packaging) - certified by DIN CERTCO (Registration number: 8C428), a certification company of the TÜV Rheinland Group
- Nearly invisible: The paper adhesive tape blends in on light-colored surfaces and is copy-neutral
- Extremely versatile: For everyday use, gift wrapping and labeling
- Perfect for paper and book pages: Text readability is not affected thanks to transparent tape
- Simple and safe: The adhesive tape can be easily torn by hand - suitable for children
- Easy organization: Ideal for writing with permanent markers, also with pencils and ballpoint pens
- Practical: The tape holds reliably thanks to water-based acrylic adhesive
- INGEDE12 certified: tesafilm® PAPER does not harm the recycling process of paper and cardboard
- Made of paper from well-managed, certified forests and other controlled sources

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing material | Paper | • Total thickness | 50 µm |
| • Type of adhesive | water-based acrylic | | |

tesafilm® PAPER

Product Information

Properties/Performance Values

• Tensile strength	30 N/cm	• Solvent free	yes
• Acid-free	yes	• Suitable surfaces	Cardboard, Paper
• Ageing resistance (UV)	yes	• Tear resistance	no
• Hand tearability	yes	• Transparency	good
• Low noise unwinding	yes	• Unwind force n/cm	1 N/cm
• Photocopy neutral	yes	• Writable	yes

Certificates

Certified according to

- INGEDE12 (validity: 2024-06-13)
- Din Certco (validity: 2024-12-17 to 2030-12-31)

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=59211A>